

DRAM MODEL SPECIFICATIONS

DRAM Specifications	2" DRAM	Spl. 1 1/4" DRAM
Non-Retractable (Fixed Flange)	Yes	Yes
Retractable (R)	Yes	Yes
Plasma Flame Detection (PFD)	Yes	Yes
Non-Flame Detection (NFD)	Yes	Yes
Cool Tip (CT)	Yes	Yes
Flex Length	As Specified By Customer	As Specified By Customer
Terminal Strips (TS)	As Specified By Customer	As Specified By Customer
Flange Size	As Specified By Customer	As Specified By Customer
Required Hole Diameter	3" or Larger	2" or Larger
Pilot Length	As Specified By Customer	As Specified By Customer
Air Connection Size	1/2" NPT	1/2" NPT
Gas Connection Size	1/2" NPT	1/2" NPT
Normal Operating Gas Pressure	30 PSI	As Specified By Application
Normal Operating Air Pressure	30 PSI	As Specified By Application
Maximum Vessel Pressure	0 -15 PSIG	0 -55 PSIG
Primary BTU Heat Release	30K	30K
Secondary BTU Heat Release	50K - 500K	50K - 150K
Total Maximum BTU Heat Release	530K	180K
Pilot Construction Material	Stainless Steel 304/310	Stainless Steel 304/310